

EP Series

10-800kVA

3:3 phase P.F. : 0.9



www.shinozawa.co.th



Control Panel



500kVA



300kVA

FEATURES

• Online double conversion

Adopting Online Double Conversion design.

UPS transfers among different working mode without output interruption, thereby powering the load uninterruptedly.

• Full DSP control

Full DSP Control avoids the risks caused by analog devices failure and makes the control system more stable and reliable.

• High power factor

The output power factor is up to 0.9

The input power factor 0.98 with filter helps to improve the efficiency, reduce the harmonic pollution to the Grid and lower the UPS running cost.

• Wide input adaptability

The range of AC input voltage is (380Va/400Vac/415Vac) (-25%/+20%) minimizing the chance of transferring to battery mode, thereby greatly prolonging the battery life.

Wide input frequency ranging from 45Hz to 65Hz. Compatible with all kinds of UPS.

• Optimized battery management

Intelligent battery management system and advanced battery auto float/boost charge technology, reduces the frequency of battery maintenance, greatly improves the battery efficiency and extends battery life.

Battery discharge time prediction: the system will display the backup time of battery calculated by discharge current and voltage.

Battery self-test: battery is automatically tested at regular intervals

Flexible battery configuration ranging from 360~408Vdc / 480Vdc.

• N+X parallel redundancy

N+X parallel redundant design, up to 6 units available, makes the configuration more flexible.

Any unit in parallel system fails, the faulty one will automatically cut off the output, and the load will be powered by the remained units.

It is easy to configure the parallel system just by connecting the parallel cables and doing corresponding settings.

Non-fixed Master-Slave relationship: Among several UPS in parallel, the unit startup first is Master UPS, the others are Slave. The master and slave may be exchanged.

• Strong overload capability

110% / 125% / 150% overload for 60min / 10min / 1min.

• Power walk in

Specially designed power walk in function, in which rectifier of each unit in parallel system will be turned on in sequence at intervals to avoid the sudden load on the generator, thereby reducing the capacity of the generator required.

• Generator mode

Set the maximum output power of the generator when a smaller one than needed is employed to extend the battery duration time. In this case, the load is supplied by both the generator and battery.

• LBS synchronization

Synchronize the output of the two independent UPS systems (single unit or parallel) even when the two systems are operating on different modes (bypass/inverter) or on battery.

• Multi-protection

Self-diagnosis function will take place before start-up for safety.

Multi-protection: AC input under/over voltage, overload, short-circuit, over-current, over bus voltage, over-temperature, fan failure, auxiliary power failure, battery under voltage, battery over-charge and so on.

• EPO function

A concave red EPO button with transparent cover is embodied in the LCD control panel for emergency power off.

• User-friendly network management

LCD and LED mimic diagram: real time operation parameters and status

RS232 & RS485 communication ports: for local monitor with corresponding software, and MODBUS protocol is optional.

SNMP adapter (optional): for remote monitor through network

Dry contacts for additional monitoring

- a) UPS on Inverter
- b) Mains input failure
- c) Remote EPO
- d) Battery low voltage alarm
- e) UPS fault
- f) UPS alarm
- g) UPS on battery
- h) UPS on bypass
- N otetd)--h) optional

TECHNICAL SPECIFICATION :

MODEL	EP100	EP200	EP300	EP400	EP600	EP800
Capacity (VA/Watts)	10k/9k	20k/18k	30k/27k	40k/36k	60k/54k	80k/72k
INPUT						
Operating Voltage Range	380 / 400 / 415 VAC (-25% - +20%), 3 Phase + N + PE)					
Operating Frequency Range	50 / 60 Hz (± 5Hz)					
Power Factor	>0.97 (with Filter)					
OUTPUT						
Output Voltage	380 / 400 / 415 VAC (1±1%)					
Output Frequency	50 / 60 Hz (1±0.05%)					
Current Crest Ratio	3:1 (Max)					
Efficiency	≥88%	≥89%		≥90%		≥90.5%
Harmonic Distortion (THDv)	<3% with linear load					
BYPASS						
Rated Voltage	380 / 400 / 415 VAC					
Rated Frequency	50 / 60 Hz					
Voltage Protection Range	Upper limit:+20%(+10%,+15%,+20% adjustable) Lower limit:-40%(-10%,-20%,-30%,-40% adjustable)					
Frequency Protection Range	±10%(± 2.5%, ± 5%, ± 10%, ± 20% adjustable)					
BATTERY						
Battery Voltage	384Vdc (360~384Vdc)					
SYSTEM FEATURES						
Transfer Time	Utility↔Battery : 0 ms					
Overload	≥110% : last 60 min ; ≥125% last 10 min ; ≥150% : last 1 min					
LED Display	Input, Inverter, Bypass, Output, Status					
LCD Display	I/O voltage,Frequency,Power,Power factor,Battery voltage,Current,Battery status,Load level,UPS status,History record					
Communication Interface	Dry contact,RS232,RS485,SNMP card(Optional)					
PHYSICAL						
Dimension,W×D×H(mm)	570×800×1195				880×760×1600	
Net Weight(kg)	217	273	316	330	483	525
Shipping Weight(kg)	272	328	371	385	553	595
ENVIRONMENT						
Operating Temperature	0 ~ 40°C					
Storage Temperature	-25 ~ 55°C					
Humidity Range	0 ~ 95% (Non-condensing)					
Altitude	<1500m					
Noise level	< 60dB			< 65dB		
STANDARDS						
Safety	IEC/EN62040-1 ; IEC/EN60950-1					
EMC	IEC/EN62040-2, IEC/EN61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-8					

Specifications are subject to change without prior notice.

TECHNICAL SPECIFICATION :

MODEL	EP1000	EP1200	EP1600	EP2000	EP3000	EP4000	EP5000	EP6000	EP8000
Capacity (VA/Watts)	100k/90k	120k/108k	160k/144k	200k/180k	300k/370k	400k/360k	500k/450k	600k/540k	800k/720k
INPUT									
Operating Voltage Range	380 / 400 / 415 VAC (-25% - +20%), 3 Phase + N + PE								
Operating Frequency Range	50 / 60 Hz (± 5Hz)								
Power Factor	>0.97 (with Filter)								
OUTPUT									
Output Voltage	380 / 400 / 415 VAC (1±1%)								
Output Frequency	50 / 60 Hz (1±0.05%)								
Current Crest Ratio	3:1 (Max)								
Efficiency	≥92%	≥92.5%	≥93%	≥93.5%	≥94%				
Harmonic Distortion (THDv)	<2% with linear load								
BYPASS									
Rated Voltage	380 / 400 / 415 VAC								
Rated Frequency	50 / 60 Hz (Auto-sensing)								
Voltage Protection Range	Upper limit:+20%(+10%,+15%,+20% adjustable) Lower limit:-40%(-10%,-20%,-30%,-40% adjustable)								
Frequency Protection Range	± 10%(± 2.5%, ± 5%, ± 10%, ± 20% adjustable)								
BATTERY									
Battery Voltage	384Vdc(360~384Vdc)						480Vdc		
SYSTEM FEATURES									
Transfer Time	Utility↔Battery : 0 ms								
Overload	≥110% : last 60 min ; ≥125% last 10 min ; ≥150% : last 1 min								
LED Display	Input, Inverter, Bypass, Output, Status								
LCD Display	I/O voltage,Frequency,Power,Power factor,Battery voltage,Current,Battery status,Load level,UPS status,History record,Settings								
Communication Interface	Dry contact,RS232,RS485,SNMP card(Optional)								
Optional	Harmonic filter,SNMP adapter,LBS cables,Battery temperature sensor,Bypass current-sharing inductor								
PHYSICAL									
Dimension,W × D × H (mm)	1160 × 805 × 1600(6P) 1520 × 830 × 1600(12P)	1400 × 945 × 1900(6P) 1640 × 1040 × 1900(12P)	1640 × 1040 × 1900(6P) 1760 × 1040 × 1900(12P)	2800 × 1040 × 1900(12P)		3900 × 1100 × 1950(12P)			
Net Weight(kg)	800/1100	903/1250	1219/1774	1425/1893	1780/2580	2 050/3050	3700	4500	6400
Shipping Weight(kg)	890/1190	993/1293	1349/1954	1555/2073	1950/2850	2200/3300	3950	4750	6700
ENVIRONMENT									
Operating Temperature	0 ~ 40°C								
Storage Temperature	-25 ~ 55°C								
Humidity Range	0 ~ 95% (Non-condensing)								
Altitude	<1500m								
Noise level	< 65dB				< 70dB				
STANDARDS									
Safety	IEC/EN62040-1 ; IEC/EN60950-1								
EMC	IEC/EN62040-2, IEC/EN61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-8								

Specifications are subject to change without prior notice.



SHINOZAWA (THAILAND) CO.,LTD.
89/209 Hathairat Road Bangchan,
Klongsamwa, Bangkok Thailand 10510
Tel. / Fax. : +66(0) 2077 4782
E-mail : support@shinozawa.co.th
Website : shinozawa.co.th

Distributed By :